

—— P L U S + ——

# **UPRIGHT DISPLAY COOLER - 7.7 CU Ft.**

P-IM08MR-W

Energy efficient, eco-friendly HC refrigerant with low charge, spark-free components, and the lowest utility costs in its category.









DOE

## **KEY FEATURES**

Eco-Friendly Refrigerant

Environmentally friendly hydrocarbon refrigerant has low Global Warming Potential (GWP). Meets all USA & California refrigerant & energy standards.

Electronic Temperature Controller
 Patented ETC1H electronic controller assures optimal

Patented ETC1H electronic controller assures optimal refrigeration performance through precision temperature control, and intelligent control for defrost cycle, compressor & other component functions.

- High Power Reliable Refrigeration System Fast pull down, optimal internal air circulation and reliable refrigeration, maintaining colder temperatures for food preservation.
- Newly Designed Condenser

New condenser featuring a joints reduction down to zero increasing long term refrigeration reliability and safeguarding against any system leaks.

• Standard LED Lighting System

Ultra-bright low energy interior LED illumination system provides optimal merchandise display visibility. Low profile, door mounted, clip-in LED design.







# **UPRIGHT DISPLAY COOLER - 7.7 CU Ft.**


## P-IM08MR-W

#### PRODUCT VIEWS



#### **FRONT VIEW**







This equipment is intended for the storage and display of bottled or canned products. This display refrigerator is not for the display of potentially hazardous foods.

Exterior Dimensions		Interior Dimensions			
H:	72 1/2"	184 cm	H:	52 7/8"	135 cm
W:	20 1/4"	51 cm	W:	15 7/8"	40 cm
D:	22 5/8"	58 cm	D:	16 3/4"	42 cm
Usa	ble Interio	or Capacity	Usa	ble Volum	e
H:	45 1/2"	116 cm	7.7	ft <sup>3</sup>	
W:	14 5/8"	37 cm	217	.8 lts	
D:	14 1/8"	36 cm			

	2001 0011501 0001011				
1	V7 Plastic frame	5		15 1/8" 14 5/8"	
	l		D:	14 3/0	37 CITI

External Material Pre-painted steel Internal Material Pre-painted steel

## REFRIGERATION PERFORMANCE DATA

Refrigerant		Energy Consumption		
	R600a 1.6 Oz (0.045 kg)	1.160 kWh/24h		
	Compressor Power	Condenser		
	1/8 HP	Finless (low maintenance)		
	Thermostat setting default	<b>Cut-Out Cut-In</b> 32°F (0°C) 44.6°F (7°C)		

### ELECTRICAL DATA

<b>Power supply</b> 115V/60 Hz	1.8 A	Lighting 394.1 Lux Output 7 modules 8 LED per module
Plug Type 🔫	Controller	Cord lenght
NEMA 5-15P	ETC1H	118" (3000 mm)

- Warranties are not supported outside the continental United States.
- Warranties are not transferable to other parties.
- Warranties do not cover the loss of product or income due to equipment malfunctioning.
- Placing the equipment outdoors, using it to store hazardous materials or modifying the equipment in any way voids all warranties.