

3 DOOR DISPLAY COOLER

P-IM72MR3-W

Energy efficient, eco-friendly HC refrigerant with low charge, spark-free components, and the lowest utility costs in its category.









DOE

KEY FEATURES

Eco-Friendly Refrigerant

Environmentally friendly hydrocarbon refrigerant has low Global Warming Potential (GWP). Meets all USA & California refrigerant & energy standards.

• Electronic Temperature Controller

Patented ETC1H electronic controller assures optimal refrigeration performance through precision temperature control, and intelligent control for defrost cycle, compressor & other component functions.

- High Power Reliable Refrigeration System Fast pull down, optimal internal air circulation and reliable refrigeration, maintaining colder temperatures for food preservation.
- Newly Designed Condenser

New condenser featuring a joints reduction down to zero increasing long term refrigeration reliability and safeguarding against any system leaks.

Standard LED Lighting System

Ultra-bright low energy interior LED illumination system provides optimal merchandise display visibility. Low profile, door mounted, clip-in LED design.








3 DOOR DISPLAY COOLER

P-IM72MR3-W

PRODUCT VIEWS









This equipment is intended for the storage and display of bottled or canned products. This display refrigerator is not for the display of potentially hazardous foods.

xt	erior Dime	ensions	Inte	rior Dime	nsions
H:	79 3/8"	202 cm	H:	60 1/8"	152 cm
W:	78 3/4"	200 cm	W:	74 5/8"	190 cm
D:	33 5/8"	86 cm	D:	27 1/4"	69 cm
Usa	ble Interio	or Capacity	Usa	ble Volum	е
H:	52 5/8"	134 cm	66.3	3T ft ³	
W:	72 1/8"	183 cm	187	8.4 lts	
D:	21 5/8"	55 cm			

Door S Door Construction		Silettes	SHELVESSIE			
3	V7 Plastic frame	15		24 1/2"	62 cm	
			D:	22 1/8"	56 cm	
	al Material Pre-pain					

REFRIGERATION PERFORMANCE DATA

Refrige	rant	Energy Consumption		
R290	5.6 Oz (0.160 kg)	5.004 kWh/24h		
Compre	essor Power	Condenser		
1/2 HP	x 2	Finless (low maintenance)		
Therm	ostat setting default	Cut-Out 32°F (0°C)	Cut-In 44.6°F (7°C)	

(1) ELECTRICAL DATA

115V/60 Hz	13.6 A	242 Lux Output 27 modules 8 LED per module
Plug Type 🔑	Controller	Cord length
NEMA 5-15P	ETC1H	118" (300 cm)

- Warranties are not supported outside the continental United States
- All warranties valid from date of purchase and are not transferable to other parties.
- Warranties do not cover the loss of product or income due to equipment malfunction.
- Placing the equipment outdoors, using it to store hazardous materials or modifying the equipment in any way voids all warranties.

Lighting